

Technical Data Sheet

Potassium Silicate Liquid				
Product Name		Potassium Silicate Liquid		
Product Code		KL-40B		
<u>Technical Data Sheet (Properties)</u>				
<u>Chemical Properties</u>				
Sr. NO	Characteristic	Unit	Specification	Test Method
1	Weight. Ratio	-	2.0 - 2.2	IS-14212:1995
2	Molar. Ratio	-	3.12 -3.43	IS-14212:1995
3	K ₂ O Content	%	12-14	IS-14212:1995
4	SiO ₂ Content	%	26-28	IS-14212:1995
5	Total Solid	%	38-42	IS-14212:1995
<u>Physical Properties</u>				
6	Appearance	-	Colorless Liquid	Visually
8	Baume (Degree) at 27 °C	^o Be	39-41	IS-14212:1995
9	Sp Gravity	-	1.380-1.400	IS-14212:1995

Packing, Loading & Shelf life.

Packing	50KG,100KG,250KG,300KG HDPE Drums , 1300 to 1400 KG IBC Tank Tanker loading – 10 to 30 MT
Loading – W/o Pallet	50KG,100KG,250KG,300KG – 20 to 24 MT/20FCL 1300-1400 KG IBC Tank – 22 to 25 MT/20FCL
Loading – On Pallet	50KG & 100KG – 18 to 20MT/20FCL 250KG & 300KG – 22 to 26 MT/20FCL
Shelf Life	24 Month under proper storage condition*

*** Proper Storage condition: Keep container tightly closed, keep in cool, dry and ventilated place, and avoid strong acid.**

FIRM: GUJ-RJT- 82504 GSTIN: 24AARFP2558H1ZX UAN: GJ32B0000361 CST / TIN: 24592010892 ISO 9001: 2015: TQS QMS/20180422320 CE MARKING: CE / 20180422321 IEC: AARFP2558H	Ankit Silicate Survey No-259, P-3 B/H Nilkanth Ceramic Jetpar Road, At- Bela, Morbi - 363642, Gujarat (India). E-Mail: sales@ankitsilicate.com Website: www.ankitsilicate.com
---	--