

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE

Product identifier

Product Name Sodium Silicate Powder

Alternative names Sodium silicate, powder, Granular

CAS No. 1344-09-8 EINECS No. 215-687-4

Relevant identified uses of the substance or mixture and uses advised against

Identified use(s) General purpose industrial chemical for use in a wide range of

applications.

Details of the supplier of the safety data sheet

Company Identification: ANKIT SILICATE

Survey No-259, P-3 B/H Nilkanth Ceramic Jetpar Road, At- Bela, Morbi - 363642, Gujarat (India). export@ankitsilicate.com

Email:

Emergency Telephone number

Emergency Phone No. +91 9712796836

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture GHS Classification

H319 : Serious eye damage/irritation Category 2 H315 : Skin corrosion/irritation Category 2

H335 : STOT - single exposure Category 3

Label elements



Hazard statement(s) H315: Causes skin irritation.

H319: Causes serious eye irritation. H335: May cause respiratory irritation.



Precautionary statement(s)

P261: Avoid breathing dust.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash (hands and exposed skin) thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Other hazards Not Calcified as PBT substance

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	%W/W	Hazard symbol(s) and
Silicic acid, sodium salt	>99 Powder	hazard statement(s) Eye Dam. 1; Skin Irrit.2; STOT SE 3

SECTION 4: FIRST AID MEASURES

Description of first aid measures

Eye Contact Irrigate with eyewash solution or clean water, holding the eyelids

apart, for at least 15 minutes. Obtain immediate medical

attention.

Skin Contact Wash affected skin with plenty of water. If symptoms develop,

obtain medical attention.

Inhalation Remove patient from exposure, keep warm and at rest. Obtain

medical attention.

Ingestion Do not induce vomiting. Wash out mouth with water and give

200-300 ml (half a pint) of water to drink. Obtain medical

attention.

Most important symptoms and effects, both acute and

delayed

Alkaline.

Causes serious eye irritation

Irritating to respiratory system and skin.

The toxicity of sodium silicate is dependent on the silica to alkali

ratio and on the pH.

Indication of any immediate medical attention and special

treatment needed

Obtain immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media Unsuitable extinguishing Media Compatible with all standard firefighting techniques.

None known.



Special hazards arising from the substance or mixture

Advice for fire-fighters

Not applicable. Inorganic powder or granules. Non-combustible.

None.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Wear eye/face protection. An approved dust mask should be worn if dust is generated

during handling. See Section: 8.2

Environmental precautions

Do not allow to enter drains, sewers or watercourses. Advise Authorities if spillage has entered water course or sewer or has

contaminated soil or vegetation.

Methods and materials for containment and cleaning up

Caution - spillages may be slippery. Avoid generation of dust. Sweep or preferably vacuum up and collect in suitable containers

for recovery or disposal.

Reference to other sections See Also Section 8.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Avoid contact with eyes, skin and clothing.

Avoid generation of dust.

Emergency shower and eye wash facilities should be readily

available.

See Also Section 8.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed and dry. Unsuitable containers: Aluminum

See Also Section 10.

Specific end use(s) See also Annex to the extended Safety Data Sheet.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

SUBSTANCE.	Occupational Exposure Limits
Silicic acid, sodium salt	No Occupational Exposure Limit assigned. An exposure limit of 2 mg/m3 (15 min TWA) is recommended by analogy with sodium hydroxide (UK EH40).

Exposure controls Wear protective equipment to comply with good occupational

hygiene practice. Do not eat, drink or smoke at the work place. Engineering methods to prevent or control exposure are

Appropriate engineering controls

Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of

process conditions.

Personal Protection

Respiratory protection Avoid inhalation of dusts. Wear suitable respiratory protective

equipment if working in confined spaces with inadequate ventilation or where there is any risk of the exposure limits being exceeded. Advice on respiratory protective equipment is given in the HSE (Health and Safety Executive) publication HS(G)53.

Dust mask: FFP2 (EN 149). Chemical goggles (EN 166).

Eye/face protection



Skin protection Wear suitable protective clothing and gloves.

Plastic or rubber gloves. For example EN374-3, level 6

breakthrough time (>480min).

Wear suitable overalls. For example EN ISO 13982 (dust), EN

14605 (liquid splashes).

Environmental Exposure

Controls

The primary hazard of sodium silicate is the alkalinity. Avoid

generation of dust. Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Powder. White.
Odour
Odour Threshold (ppm) Not applicable.
pH (Value) Alkaline.
Freezing Point (°C) Not applicable.

Melting Point (°C) > 1000

Boiling Point (°C) Not applicable. Flash Point (°C) [Closed cup] Not applicable. Evaporation rate Not applicable. Flammability (solid, gas) Not applicable. Explosive Limit Ranges Not applicable. Vapour Pressure (mm Hg) Not applicable. Vapour Density (Air=1) No data. Density (g/ml) No data. Solubility (Water) Soluble. Solubility (Other) No data. Partition Coefficient No data. Auto Ignition Point (°C)

Auto Ignition Point (°C)

Decomposition Temperature (°C)

Viscosity (mPa. s)

Explosive properties

Oxidizing Properties

Other information

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Not applicable.

SECTION 10: STABILITY AND REACTIVITY

Reactivity See Section: 10.3

Chemical stability Stable.

Possibility of hazardous When arc welding vessels containing aqueous solutions of this

material, take care to control any explosion risk from hydrogen evolved by electrolysis. Aqueous solutions will react with aluminum, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Can react violently if in

contact with acids. Can react with sugar residues to form carbon

monoxide.

Conditions to avoid Incompatible materialsSee Section: 10.3
See Section: 10.3

Hazardous decomposition Hydrogen

product(s)

reactions

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Ingestion All symptoms of acute toxicity are due to high alkalinity. Material

will cause irritation. Oral LD50 (rat) 3400 mg/kg bw

Inhalation Dust is irritant to the respiratory tract. All symptoms of acute

toxicity are due to high alkalinity. Inhalation LC50 (rat) >2.06 g/m³



Skin Contact Material will cause irritation. Dermal LD50 (rat) >5000 mg/kg bw Eye Contact Material will cause severe irritation. Risk of serious damage to

eves.

Skin corrosion/irritation Irritating to skin. Serious eye damage/irritation Irritating to eyes. Sensitization Not sensitizing.

Mutagenicity No evidence of genotoxicity. In vitro/in vivo negative.

Carcinogenicity No structural alerts

Reproductive toxicity No evidence of reproductive toxicity or developmental toxicity.

STOT - single exposure Irritating to respiratory system.

STOT - repeated exposure Prolonged or repeated inhalation of crystalline silica causes lung

diseases including silicosis, emphysema, obstructive airway

disease and lung cancer.

Aspiration hazard Not classified

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Fish (Brachydanio rerio) LC50 (96 hour) 1108 mg/l

Aquatic invertebrates: (Daphnia magna) EC50 (48 hour) 1700

Inorganic. The substance has no potential for bioaccumulation.

ma/l

Persistence and Inorganic. Soluble silicates, upon dilution, rapidly depolymerise into molecular species indistinguishable from natural dissolved degradability

Bioaccumulative potential

Mobility in soil

Not applicable. Results of PBT and vPvB Not classified as PBT or vPvB.

assessment

Other adverse effects The alkalinity of this material will have a local effect on

ecosystems sensitive to changes in pH.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Discharge of this product to sewage treatment works is

> dependent on local regulations with regard to pH controls. Dispose of this material and its container to hazardous or special

waste collection point.

Disposal should be in accordance with local, state or national

legislation.

Not applicable.

SECTION 14: TRANSPORT INFORMATION

UN number Not applicable **Proper Shipping Name** Not applicable. Transport hazard class(es) Not applicable. Packing group Not applicable.

Not classified as a Marine Pollutant. **Environmental hazards** Special precautions for user No special packaging requirements. Unsuitable containers: Aluminum

Transport in bulk according to Annex II of MARPOL73/78 and

the IBC Code



SECTION 15: REGULATORY INFORMATION

- 15.1 Chemical Safety Assessment
- 15.2 Safety, health and environmental regulation/legislation specific for the substance or mixture

SECTION 16: OTHER INFORMATION

The Information on This Safety Data Sheet Is Believed to Be Accurate and It Is the Best Information Available.

No Liability Resulting from The Use or Handling of The Product to Which This Safety Data Sheet Relates. Users and Handlers of This Product Should Make Their Own Investigations to Determine the Suitability of The Information Provided Herein for Their Own Purposes.